

■セレクションガイド

| シリーズ | 出力 | 入力電圧 | 出力 | | | 定電圧回路 | 動作保証温度 | 形状 | サイズ(mm) | 絶縁耐圧(VDC) | | | |
|--------|----------|--------------------------|--|---|---|-------|--|-------|---|-----------|-------|-------|-------|
| | | | 出力電圧 | S | D | | | | | 1.0k | 1.5 k | 3.0 k | 6.0 k |
| SR | 0.5W~1W | 5,12,24,48 (±10%) | 5.9,12,15 | ● | | ● | -25°C~+71°C | DIP16 | 22.6×9.9×8.4 | ● | | | |
| S | 0.5W~2W | 5,12,24,48 (±10%) | 3.3,5,9,12,15,24 | ● | | - | -25°C~+71°C | DIP16 | 22.6×9.9×8.4 | ● | | | |
| LA | 1W | 3.3,5,12,24,48 (±10%) | 5.9,12,15 | ● | | - | -25°C~+80°C | DIP8 | 12.7×10.2×7.1 12.7×10.2×7.6 | ● | | | |
| LA-LH | 1W | 3.3,5,12,24 (±10%) | 3.3,5,9,12,15 ±5,±12,±15 | ● | ● | - | -40°C~+85°C | DIP8 | 12.7×10.2×7.1 12.7×10.2×7.6 | | | ● | |
| LV | 1W~2W | 3.3,5,12,24,48 (±10%) | 5.9,12,15 | ● | | - | -25°C~+80°C | SIP4 | 11.7×6.0×10.2 11.7×7.5×10.2 14.0×7.5×10.2 | | ● | | |
| VD | 1W | 5,12,24 (±10%) | ±5,±12,±15 | | ● | - | -25°C~+80°C | DIP14 | 20.3×10.2×7.1 | ● | | | |
| VS | 1W | 5,12,24 (±10%) | 3.3,5,9,12,15 ±5,±12,±15 | ● | ● | - | -25°C~+80°C | SIP7 | 19.6×6.1×10.2 19.6×7.1×10.2 | ● | | ● | |
| VS020 | 2W | 3.3,5,12,24 (±10%) | 3.3,5,9,12,15,24 ±5,±9,±12 ±15,±18,±24 | ● | ● | - | -40°C~+71°C | SIP7 | 19.6×7.1×10.2 | | ● | ● | |
| VS030 | 3W | 5,12,24 (±10%) | 5.9,12,15 | ● | | - | 5V: -40°C~+70°C 9V,12V,15V: -40°C~+65°C | SIP7 | 19.6×7.5×10.2 | | | ● | |
| VSS | 1W | 5,12,24 (±10%) | 5.9,12,15 | ● | | - | -25°C~+80°C | SIP7 | 19.6×7.5×10.2 | | | ● | |
| VW | 1W | 12,24,48 (2:1) | 3.3,5,12,15 | ● | | ● | -40°C~+75°C | SIP6 | 17.4×7.75×11.1 | | ● | | |
| VSW | 1.8W~3W | 5,12,24,48 (2:1) | 5.9,12,15,24 | ● | | ● | -40°C~+85°C | SIP8 | 21.8×9.2×11.1 | | ● | ● | |
| SMA/SM | 1W~2W | 3.3,5,12,24 (±10%) | 3.3,5,9,12,15 | ● | | - | -40°C~+85°C | SMD | 13.8×12.8×9.3 25.4×12.8×9.3 | ● | | | |
| BW | 3W~6W | 5,12,24,48 (2:1/4:1) | 3.3,5,9,12,15 ±5,±12,±15 | ● | ● | ● | -40°C~+71°C | DIP24 | 31.8×20.3×12.2 | | ● | ● | |
| BW-6K | 3W~6W | 5,12,24,48 (2:1) | 5.9,12,15 ±5,±12,±15 | ● | ● | ● | -40°C~+85°C | DIP24 | 31.8×20.3×10.2 | | | | ● |
| BW120 | 7.5W~12W | 12,24,48 (2:1) | 2.5,3.3,5,9,12,15 ±5,±12,±15 | ● | ● | ● | -40°C~+85°C | DIP24 | 31.8×20.3×12.2 | | ● | | |

・S : シングル出力 ・D : デュアル出力 ・Reg : Nは非安定化出力(出力電圧は、入力電圧に比例) Rは、安定化出力 ・一部受注生産品あり